

[Home](#) > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [DDR I and DDR II Buffers](#) > [Zero Delay Buffers](#) > [93777](#) > [93777BFIT](#)

[Add to myIDT \[?\]](#)

You may also like...

## 93777BFIT


**Category:** Zero Delay Buffers

**Generic Part:** 93777

**Market Group:** PC CLOCK

**Description:** PC BUFFER

Product Description/Features:   
 • Max frequency supported = 266MHz (DDR 533)   
 • Low skew, low jitter PLL clock driver   
 • I2C address selection for dual buffer application   
 • I2C for functional and output control   
 • Feedback pins for input to output synchronization   
 • Spread Spectrum tolerant inputs   
 • 3.3V tolerant CLK\_INT input



### Parameters

Package	SSOP 28 (PY28)
Voltage	3.3 V
Package	SSOP 28
Speed	NA
Temperature	I
Status	Active
Sample	No
Minimum Order Quantity	1000
Factory Order Increment	1000

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Description	SSOP 5.3 MM
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	240°C
Rebake Conditions	NA
Length	10.2
Mark	R
Width	5.3
Pitch	0.65
Thickness	1.73
Status	Active