

	Specifications of IME12-04BPPZW2K	
PART NUMBER	IME12-04BPPZW2K	
MANUFACTURER	N/A	
DESCRIPTION	SHRT SHLF PNP COMP CBL	
LEAD FREE STATUS / ROHS STATUS		
QUANTITY AVAILABLE	1580 pcs	
DATA SHEET		
VOLTAGE - SUPPLY	10 V ~ 30 V	
TERMINATION STYLE	Cable	
SHIELDING	Shielded	
SERIES	-	
SENSOR TYPE	Inductive	
SENSING DISTANCE	0.157" (4mm)	
RESPONSE FREQUENCY	2kHz	
PACKAGE / CASE	Cylinder, Threaded - M12	
OUTPUT TYPE	PNP-NC/NO, 4-Wire	
OTHER NAMES	1056423	
OPERATING TEMPERATURE	-25°C ~ 75°C (TA)	
MATERIAL - BODY	Plastic	
INGRESS PROTECTION	IP67	
INDICATOR	LED	
DETAILED DESCRIPTION	Inductive Proximity Sensor 0.157" (4mm) IP67 Cylinder, Threaded - M12	

Related Tags

	-	
IME12-04BPPZW2K	IME12-04BPPZW2K Distributor	IME12-04BPPZW2K Supplier
IME12-04BPPZW2K Price	IME12-04BPPZW2K Pictures	IME12-04BPPZW2K Image
IME12-04BPPZW2K PDF Datasheet	IME12-04BPPZW2K Download Datasheet	IME12-04BPPZW2K Datasheet
IME12-04BPPZW2K Stock	Buy IME12-04BPPZW2K	Buy IME12-04BPPZW2K
IME12-04BPPZW2K	Supplier	Distributor

Related Products

