N/A Image may be representation. See specifications for product details.

WTB4S-3P3204HS01

Part Number:

Manufacturer/Brand:

Product description Datasheets:

Ship From

Stock Condition

Shipment Way

WTB4S-3P3204HS01

N/A

LO ET M8 4PIN 150MM HYGN

DHL/Fedex/TNT/UPS/EMS

240 pcs stock

Hong Kong

**REQUEST FOR QUOTATION** 

MANUFACTURER  DESCRIPTION  LO E  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  SERIES  W4S- SENSING METHOD  Proxit  SENSING DISTANCE  0.157  RESPONSE TIME  OUTPUT CONFIGURATION  PNP  OTHER NAMES	30 V 3 Inox Hygiene
DESCRIPTION  LO E  LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  SERIES  W4S- SENSING METHOD  Proxi SENSING DISTANCE  0.157  RESPONSE TIME  OUTPUT CONFIGURATION  PNP OTHER NAMES	os v 30 V B Inox Hygiene
LEAD FREE STATUS / ROHS STATUS  QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  SERIES  W4S- SENSING METHOD  Proxit SENSING DISTANCE  0.157  RESPONSE TIME  OUTPUT CONFIGURATION  PNP OTHER NAMES	os v 30 V B Inox Hygiene
QUANTITY AVAILABLE  DATA SHEET  VOLTAGE - SUPPLY  SERIES  W4S- SENSING METHOD  Proxi SENSING DISTANCE  RESPONSE TIME  OUTPUT CONFIGURATION  PNP OTHER NAMES  240 p	30 V 3 Inox Hygiene
DATA SHEET  VOLTAGE - SUPPLY  SERIES  W4S- SENSING METHOD  Proximal SENSING DISTANCE  RESPONSE TIME  OUTPUT CONFIGURATION  OTHER NAMES  OUTPUT SHEET  10 V  10 V	30 V 3 Inox Hygiene
VOLTAGE - SUPPLY 10 V  SERIES W4S- SENSING METHOD Proxi  SENSING DISTANCE 0.157  RESPONSE TIME 500µ2  OUTPUT CONFIGURATION PNP  OTHER NAMES 1048	3 Inox Hygiene
SERIES W4S- SENSING METHOD Proxit SENSING DISTANCE 0.157 RESPONSE TIME 500µ2 OUTPUT CONFIGURATION PNP OTHER NAMES 1048	3 Inox Hygiene
SENSING METHOD Proxis  SENSING DISTANCE 0.157  RESPONSE TIME 500µs  OUTPUT CONFIGURATION PNP  OTHER NAMES 1048	
SENSING DISTANCE 0.157 RESPONSE TIME 500µ OUTPUT CONFIGURATION PNP OTHER NAMES 1048	nity
RESPONSE TIME 500µs OUTPUT CONFIGURATION PNP OTHER NAMES 1048	,
OUTPUT CONFIGURATION PNP OTHER NAMES 1048	~ 11.024" (4mm ~ 280mm)
OTHER NAMES 1048	
OPERATING TEMPERATURE -30°C	32
	~ 70°C (TA)
LIGHT SOURCE Red (	550nm)
INGRESS PROTECTION IP66	
CONNECTION METHOD Cable	with Connector
CABLE LENGTH 5.906	
ADJUSTMENT TYPE Adjus	(150.00mm)

**Related Tags** 

WTB4S-3P3204HS01	Supplier	Distributor
WTB4S-3P3204HS01 Stock	Buy WTB4S-3P3204HS01	Buy WTB4S-3P3204HS01
WTB4S-3P3204HS01 PDF Datasheet	WTB4S-3P3204HS01 Download Datasheet	WTB4S-3P3204HS01 Datasheet
WTB4S-3P3204HS01 Price	WTB4S-3P3204HS01 Pictures	WTB4S-3P3204HS01 Image
WTB4S-3P3204HS01	WTB4S-3P3204HS01 Distributor	WTB4S-3P3204HS01 Supplier

**Related Products** 

