

PART NUMBER PBT-RPIKOSNISSOALAOZ MANUFACTURER N/A DESCRIPTION SEN PRESS 0-1000 PSI LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 568 pcs DATA SHEET VOLTAGE - SUPPLY 8 V ~ 35 V TERMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current OUTPUT 4 m A ~ 20 m A OTHER NAMES 6048524 OPERATING TEMPERATURE 0°C ~ 80°C OPERATING PRESSURE 1.00.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 m A ~ 20 m A Cylinder, Metal ACCURACY ±196		Specifications of PBT-RP1K0SN1SS0ALA0Z
MANUFACTURER MANUFACTURER SEN PRESS 0-1000 PSI LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 568 pcs DATA SHEET VOLTAGE - SUPPLY 8 V ~ 35 V TERMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - PRESSURE TYPE Gauge PORT STYLE PORT STYLE PORT STYLE PACKAGE / CASE CYINDER, Metal OUTPUT 'A Manuel Analog Current OUTPUT OTHER NAMES OO48524 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING PRESSURE MAXIMUM PRESSURE FEATURES LEAD FRESSURE SHOP SHOP SHOP SHOP SHOP SHOP SHOP SHOP		
DESCRIPTION SEN PRESS 0-1000 PSI LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 568 pcs DATA SHEET VOLTAGE - SUPPLY 8 V ~ 35 V TERMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE PEMBLe - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING TEMPERATURE OPERATING TEMPERSSURE MAXIMUM PRESSURE FEATURES - DETAILED DESCRIPTION Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	PART NUMBER	PBT-RP1K0SN1SS0ALA0Z
QUANTITY AVAILABLE 568 pcs DATA SHEET VOLTAGE - SUPPLY 8 V ~ 35 V TEMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE OPERATING PRESSURE DETAILED DESCRIPTION PRESSURE PORT SIZE Female - 1/4" (6.35mm) NPT Analog Current OUTPUT PACKAGE / CASE OPERATING TEMPERATURE OPEC ~ 80°C OPERATING PRESSURE - FEATURES - PRESSURE Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	MANUFACTURER	N/A
QUANTITY AVAILABLE DATA SHEET VOLTAGE - SUPPLY REMINATION STYLE SUPPLIER DEVICE PACKAGE SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES OPERATING TEMPERATURE OPERATING PRESSURE MAXIMUM PRESSURE FAILED DESCRIPTION PRESSURE S6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	DESCRIPTION	SEN PRESS 0-1000 PSI
DATA SHEET VOLTAGE - SUPPLY 8 V ~ 35 V TERMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT STYLE Female - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES OPERATING TEMPERATURE O"C ~ 80°C OPERATING PRESSURE MAXIMUM PRESSURE FEATURES - PRESSURE SHOW IN 100.0 PSI (6895 kPa) Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	LEAD FREE STATUS / ROHS STATUS	
VOLTAGE - SUPPLY TERMINATION STYLE Connector SUPPLIER DEVICE PACKAGE - SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES OPERATING TEMPERATURE OPERATING PRESSURE MAXIMUM PRESSURE FEATURES - DETAILED DESCRIPTION 8 V ~ 35 V Connector Connector Gauge - Connector Connec	QUANTITY AVAILABLE	568 pcs
TERMINATION STYLE SUPPLIER DEVICE PACKAGE - SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE OPERATING PRESSURE MAXIMUM PRESSURE FEATURES - PRESSURE Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	DATA SHEET	
SUPPLIER DEVICE PACKAGE SERIES - PRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE FEATURES PRESSURE Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	VOLTAGE - SUPPLY	8 V ~ 35 V
FRESSURE TYPE Gauge PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE 0°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE FEATURES - PRESSURE Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	TERMINATION STYLE	Connector
PRESSURE TYPE Gauge Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE FEATURES - Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	SUPPLIER DEVICE PACKAGE	-
PORT STYLE Threaded PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE O°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE FEATURES - DETAILED DESCRIPTION Threaded Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	SERIES	-
PORT SIZE Female - 1/4" (6.35mm) NPT PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current 4 mA ~ 20 mA OTHER NAMES OPERATING TEMPERATURE O°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES DETAILED DESCRIPTION Fressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	PRESSURE TYPE	Gauge
PACKAGE / CASE Cylinder, Metal OUTPUT TYPE Analog Current 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE 0°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES DETAILED DESCRIPTION Cylinder, Metal Analog Current 4 mA ~ 20 mA 6048524 6048524 6048524 609°C 70°C ~ 80°C 1000.0 PSI (6895 kPa) - Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	PORT STYLE	Threaded
OUTPUT TYPE OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE 0°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION Analog Current 4 mA ~ 20 mA 0000 C ~ 80°C Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	PORT SIZE	Female - 1/4" (6.35mm) NPT
OUTPUT 4 mA ~ 20 mA OTHER NAMES 6048524 OPERATING TEMPERATURE 0°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	PACKAGE / CASE	Cylinder, Metal
OPERATING TEMPERATURE O°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION 6048524 0°C ~ 80°C 1000.0 PSI (6895 kPa) - Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	OUTPUT TYPE	Analog Current
OPERATING TEMPERATURE O°C ~ 80°C OPERATING PRESSURE 1000.0 PSI (6895 kPa) MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION O°C ~ 80°C 1000.0 PSI (6895 kPa) Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	OUTPUT	4 mA ~ 20 mA
OPERATING PRESSURE MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION 1000.0 PSI (6895 kPa) - Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	OTHER NAMES	6048524
MAXIMUM PRESSURE - FEATURES - DETAILED DESCRIPTION Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	OPERATING TEMPERATURE	0°C ~ 80°C
FEATURES - DETAILED DESCRIPTION Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	OPERATING PRESSURE	1000.0 PSI (6895 kPa)
DETAILED DESCRIPTION Pressure Sensor 1000.0 PSI (6895 kPa) Gauge Female - 1/4" (6.35mm) NPT 4 mA ~ 20 mA Cylinder, Metal	MAXIMUM PRESSURE	-
Metal Metal	FEATURES	-
ACCURACY ±1%	DETAILED DESCRIPTION	
	ACCURACY	±1%

Related Tags

PBT-RP1K0SN1SS0ALA0Z	PBT-RP1K0SN1SS0ALA0Z Distributor	PBT-RP1K0SN1SS0ALA0Z Supplier
PBT-RP1K0SN1SS0ALA0Z Price	PBT-RP1K0SN1SS0ALA0Z Pictures	PBT-RP1K0SN1SS0ALA0Z Image
PBT-RP1K0SN1SS0ALA0Z PDF Datasheet	PBT-RP1K0SN1SS0ALA0Z Download Datasheet	PBT-RP1K0SN1SS0ALA0Z Datasheet
PBT-RP1K0SN1SS0ALA0Z Stock	Buy PBT-RP1K0SN1SS0ALA0Z	Buy PBT-RP1K0SN1SS0ALA0Z
PBT-RP1K0SN1SS0ALA0Z	Supplier	Distributor

