•



E-Switch

200AWMSP1T2A1VS2QE

Product description

RoHs Status

Ship From

Stock Condition

Shipment Way

Part Number: 200AWMSP1T2A1VS2QE

Manufacturer/Brand: E-Switch

1.200AWMSP1T2A1VS2QE.pdf Datasheets: 2.200AWMSP1T2A1VS2QE.pdf

Lead free / RoHS Compliant 33271 pcs stock

> Hong Kong DHL/Fedex/TNT/UPS/EMS

SWITCH TOGGLE SPDT 3A 120V

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER  200AWMSPITZAIVS2QE  MANUFACTURER  5-Switch  DESCRIPTION  SWITCH TOGGLE SPDT 3A 120V  LEAD REEE STATUS / ROHS STATUS  LEAD REEE STATUS / ROHS STATUS  LEAD REEE STATUS / ROHS STATUS  LEAD REE STATUS / ROHS		
MANUFACTURER         E-Switch           DESCRIPTION         SWITCH TOGGLE SPOT 3A 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         33271 pro           DATA SHEET         \$\frac{1}{2}\trace{2}\tr		Specifications of 200AWMSP1T2A1VS2QE
MANUFACTURER         E-Switch           DESCRIPTION         SWITCH TOGGLE SPOT 3A 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         33271 pro           DATA SHEET         \$\frac{1}{2}\trace{2}\tr	DADT NUMBED	200AW/MSD1T2A1VS2OF
DESCRIPTION         SWITCH TOGGLE SPDT 3A 120V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         33271 pcs           DATA SHEET         1200AWKSPITZALVS2QE.pdf           VOLTAGE RATING - DC         2V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         0m-0n           SERIES         200A           PACKAGING         Bulk           OPERATING TEMPERATURE         30%C ~ 85°C           MOINTING TYPE         Through Hole           MOINTING TYPE         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LIEAD FREE STATUS / ROHS STATUS         Lead free / RoHS C		
Lead free / RoHS Compliant  QUANTITY AVAILABLE  DATA SHEET  DATA S		
QUANTITY AVAILABLE         33271 pes           DATA SHEET         1.200AWMSP1TZAIVSQE,pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         0n-On           SWITCH FUNCTION         0n-On           PAREL CUTOUT DIMENSIONS         -           PAREL CUTOUT DIMENSIONS         10k           POERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through Hole           MOUNTING TYPE         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           INGRESS PROTECTION         1P67 - Dust Tight, Waterproof           ILLUMINATION YOLTAGE (NOMINAL)         -           ILLUMINATION YPF, COLOR         50,000 Cycles           ELECTRICAL LIFE         50,000 Cycles           DETAILED DESCRIPTION         30,000 Cycles		
DATA SHEET  DATA S		
DATA SHEET         E 2200AWMSPIT2AINS QE.pdf           VOLTAGE RATING - DC         28V           VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC PIN           SWITCH FUNCTION         0n-On           SERIES         200A           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole           MOINTING TYPE         1 (Unlimited)           MESTATUS / ROHS STATUS         Lead free / ROHS Compliant           INGRESS PROTECTION         1P67 - Dust Tight, Waterproof           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         50,000 Cycles           ILLUMINATION TYPE, COLOR         50,000 Cycles           ILLUMINATION TYPE, COLOR         50,000 Cycles           ILLUMINATION TYPE, COLOR         70,000 Cycles           ILLUMINATION         70,000 Cycles           IDETAILED DESCRIPTION         70,000 Cycles           IDETAILED DESCRIPTION         70,000 Cycles           IDETAILED DESCRIPTION         70,000 Cycles           IDETAILED RESCRIPTION         70,000 Cycles           IDETAILED RESCRIPTION         70,000 Cycles	QUANTITY AVAILABLE	
VOLTAGE RATING - AC         120V           TERMINATION STYLE         PC Pin           SWITCH FUNCTION         0n-On           SERIES         200A           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LEAD FREE STATUS / ROHS STATUS         10967 - Dust Tight, Waterproof           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Non-Illuminated           ELECTRICAL LIFE         50,000C yeles           DETAILD DESCRIPTION         Toggle Switch SPDT Through Hole           CURRENT RATING         3A (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Untreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Frees, Chrome Plated	DATA SHEET	
TERMINATION STYLE         PC Pin           SWITCH FUNCTION         On-On           SERIES         200A           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         30°C ~ 85°C           MOUNTING TYPE         Through Hole           MOISTURE SENSITUITY LEVEL (MSL)         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LILUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Non-Illuminated           ELECTRICAL LIFE         50,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole           CURRENT RATING         3A (AC/DC)           CIRCUIT         SPDT           BUSHING THREAD         Untreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Brass, Chrome Plated	VOLTAGE RATING - DC	28V
SERTIES         On-On           PANEL CUTOUT DIMENSIONS         -           PACKAGIING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         -           FEATURES         Epoxy Sealed Terminals           ELECTRICAL LIFE         50,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole           CURRENT RATING         3A (AC/DC)           CURRENT RATING         5PDT           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Brass, Chrome Plated	VOLTAGE RATING - AC	120V
SERIES         200A           PANEL CUTOUT DIMENSIONS         -           PACKAGING         Bulk           OPERATING TEMPERATURE         -30°C ~ 85°C           MOUSTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           INCOMPANDA (MARCHA)         1 (P67 - Dust Tight, Waterproof           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION         Non-Illuminated           ELECTRICAL LIFE         Epoxy Sealed Terminals           ELECTRICAL LIFE         50,000 Cycles           DETAILED DESCRIPTION         Toggle Switch SPDT Through Hole           CURRENT RATING         3A (AC/DC)           BUSHING THREAD         Unthreaded           ACTUATOR TYPE         Standard Round           ACTUATOR MATERIAL         Brass, Chrome Plated	TERMINATION STYLE	PC Pin
PACKAGING BUIK  PACKAGING SUR  OPERATING TEMPERATURE 30°C ~ 85°C  MOUNTING TYPE Through Hole  MOISTURE SENSITIVITY LEVEL (MSL) 1(Unlimited)  LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant  LILUMINATION YOLTAGE (NOMINAL) 1-  LILUMINATION TYPE, COLOR 1-  LILUMINATION TYPE, COLOR 5PONY Sealed Terminals  ELECTRICAL LIFE 50,000 Cycles  DETAILED DESCRIPTION TOGGLE SWITCH SUR SUR SPONY Sealed Terminals  CURRENT RATING 3A (AC/DC)  CIRCUIT SPONY  BUSHING THREAD Unthreaded Unthreaded  ACTUATOR TYPE ACTUATED SIANG SI	SWITCH FUNCTION	On-On
PACKAGING  DPERATING TEMPERATURE  -30°C ~ 85°C  MOUNTING TYPE  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEUMINATION VOLTAGE (NOMINAL)  LLUMINATION TYPE, COLOR  LLUMINATION TYPE, COLOR  FEATURES  ELECTRICAL LIFE  DETAILED DESCRIPTION  TOGGIE SWItch SPDT Through Hole  CURRENT RATING  A (AC/DC)  CIRCUIT  BUSHING THREAD  ACTUATOR TYPE  ACTUATOR MATERIAL  BEAS, Chrome Plated  HOLD SAME AS COLOR  TROUGH AS COLOR  AS COLOR—Plated  HOLD SAME AS COLO	SERIES	200A
OPERATING TEMPERATURE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  LILUMINATION YOLTAGE (NOMINAL)  LILUMINATION TYPE, COLOR  LILUMINATION  Mon-Illuminated  FEATURES  Epoxy Sealed Terminals  ELECTRICAL LIFE  DESCRIPTION  Toggle Switch SPDT Through Hole  CURRENT RATING  ACIDATO  SPDT  BUSHING THREAD  MOTHER AGE  ACTUATOR TYPE  SEANGAR ROUND  Brass, Chrome Plated	PANEL CUTOUT DIMENSIONS	-
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILUMINATION VOLTAGE (NOMINAL) LILUMINATION TYPE, COLOR LILUMINATION TYPE, COLOR LILUMINATION SPONS Sealed Terminals ELECTRICAL LIFE DETAILED DESCRIPTION TOggle Switch SPDT Through Hole CURRENT RATING SPONS CURCUIT BUSHING THREAD ACTUATOR TYPE Standard Round ACTUATOR MATERIAL BRASS, Chrome Plated	PACKAGING	Bulk
MOISTURE SENSITIVITY LEVEL (MSL)  LEAD FREE STATUS / ROHS STATUS  LEAd free / ROHS Compliant  INGRESS PROTECTION  IP67 - Dust Tight, Waterproof  ILLUMINATION VOLTAGE (NOMINAL)	OPERATING TEMPERATURE	-30°C ~ 85°C
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINGRESS PROTECTION1P67 - Dust Tight, WaterproofILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESEpoxy Sealed TerminalsELECTRICAL LIFE50,000 CyclesDETAILED DESCRIPTIONToggle Switch SPDT Through HoleCURRENT RATING3A (AC/DC)BUSHING THREADUnthreadedACTUATOR TYPEStandard RoundACTUATOR MATERIALBrass, Chrome Plated	MOUNTING TYPE	Through Hole
INGRESS PROTECTION ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION TYPE, COLOR ILLUMINATION ILLUMINATION Mon-Illuminated FEATURES EDOXY Sealed Terminals ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION Toggle Switch SPDT Through Hole CURRENT RATING CURCUIT BUSHING THREAD Unthreaded ACTUATOR TYPE Standard Round Brass, Chrome Plated	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
ILLUMINATION VOLTAGE (NOMINAL) - ILLUMINATION TYPE, COLOR - ILLUMINATION MON-Illuminated Mon-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION TOggle Switch SPDT Through Hole CURRENT RATING 3A (AC/DC) CIRCUIT SPDT BUSHING THREAD Unthreaded ACTUATOR TYPE Standard Round ACTUATOR MATERIAL BRASS AND STANGARD SPORT Plated	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR  ILLUMINATION Non-Illuminated  FEATURES Epoxy Sealed Terminals  ELECTRICAL LIFE 50,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL BRASS STANDARD STAN	INGRESS PROTECTION	IP67 - Dust Tight, Waterproof
Non-Illuminated FEATURES Epoxy Sealed Terminals ELECTRICAL LIFE 50,000 Cycles DETAILED DESCRIPTION TOGGLE SWITCH SPDT Through Hole CURRENT RATING 3A (AC/DC) CIRCUIT SPDT BUSHING THREAD Unthreaded ACTUATOR TYPE Standard Round ACTUATOR MATERIAL BRASS CHrome Plated	ILLUMINATION VOLTAGE (NOMINAL)	-
ELECTRICAL LIFE 50,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL BEAD BEAS, Chrome Plated	ILLUMINATION TYPE, COLOR	-
ELECTRICAL LIFE 50,000 Cycles  DETAILED DESCRIPTION Toggle Switch SPDT Through Hole  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	ILLUMINATION	Non-Illuminated
DETAILED DESCRIPTION Toggle Switch SPDT Through Hole  CURRENT RATING 3A (AC/DC)  CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	FEATURES	Epoxy Sealed Terminals
CURRENT RATING 3A (AC/DC) CIRCUIT SPDT BUSHING THREAD Unthreaded ACTUATOR TYPE Standard Round ACTUATOR MATERIAL Brass, Chrome Plated	ELECTRICAL LIFE	50,000 Cycles
CIRCUIT SPDT  BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	DETAILED DESCRIPTION	Toggle Switch SPDT Through Hole
BUSHING THREAD Unthreaded  ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	CURRENT RATING	3A (AC/DC)
ACTUATOR TYPE Standard Round  ACTUATOR MATERIAL Brass, Chrome Plated	CIRCUIT	SPDT
ACTUATOR MATERIAL Brass, Chrome Plated	BUSHING THREAD	Unthreaded
	ACTUATOR TYPE	Standard Round
ACTUATOR LENGTH 6.10mm	ACTUATOR MATERIAL	Brass, Chrome Plated
	ACTUATOR LENGTH	6.10mm

# **Related Tags**

E-Switch 200AWMSP1T2A1VS2QE	200AWMSP1T2A1VS2QE Distributor	200AWMSP1T2A1VS2QE Supplier
200AWMSP1T2A1VS2QE Price	200AWMSP1T2A1VS2QE Pictures	200AWMSP1T2A1VS2QE Image
200AWMSP1T2A1VS2QE PDF Datasheet	200AWMSP1T2A1VS2QE Download Datasheet	200AWMSP1T2A1VS2QE Datasheet
200AWMSP1T2A1VS2QE Stock	Buy 200AWMSP1T2A1VS2QE	Buy E-Switch 200AWMSP1T2A1VS2QE
E-Switch 200AWMSP1T2A1VS2QE	E-Switch Supplier	E-Switch Distributor
E-Switch 200AWMSP1T2A1VS2QE		

# **Related Products**



**200AWMSP1T2A1M6QE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V In stock: 25961 pcs

**RFQ** 



### **200AWMSP2T2A1M6RE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: 22917 pcs

**RFQ** 



Manufacturers: E-Switch

**200AWMSP2T2A1M2RE** 

Description: SWITCH TOGGLE SPDT 0.4VA 20V In stock: 26155 pcs

**RFQ** 



#### **200AWMSP1T2A1M7RE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 0.4VA 20V

In stock: 26000 pcs

**RFQ** 



#### Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

**200AWMSP1T2A1M61RE** 

In stock: 22246 pcs

**RFQ** 



#### 200AWMSP2T1A1VS2QE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V In stock: 26790 pcs

**RFQ** 



# **200AWMSP1T2A1M7QE** Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V In stock: 22252 pcs

**RFQ** 



## 200AWMSP3T1A1M2QE Manufacturers: E-Switch

Description: SWITCH TOGGLE SPDT 3A 120V In stock: 30696 pcs

**RFQ** 



#### Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

**200AWMSP2T1A1M2RE** 

In stock: 33303 pcs

**RFQ** 

**200AWMSP1T2A1M6RE** Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V



#### Manufacturers: E-Switch Description: SWITCH TOGGLE SPDT 0.4VA 20V

200AWMSP1T2A1VS2RE

In stock: 26065 pcs

**RFQ** 



In stock: 23723 pcs **RFQ** 





200AWMSP1T2A1M2RE

In stock: 30592 pcs

**RFQ** 











