



IDEC



RR2BA-UDC110V

Manufacturer/Brand:

Product description

RoHs Status Stock Condition

Datasheets:

Ship From Shipment Way RR2BA-UDC110V

IDEC

RELAY GEN PURPOSE DPDT 10A 110V

RR2BA-UDC110V.pdf

Lead free / RoHS Compliant 6607 pcs stock

Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER RRZBA-UDC110V MANUFACTURER IDEC DESCRIPTION RELAY GEN PURPOSE DEDT 10A 110V LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compiliant QUANTITY AVAILABLE GEOT PES DATA SHEET TURN ON VOLTAGE (MAX) 11 VDC TURN OF VOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect - 0.187" (1.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING OPERATING TEMPERATURE 25ms QUERATING TEMPERATURE 25ms QUERATING TEMPERATURE 25ms ANDINITING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compiliant LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compiliant CONTACT RATING (CURRENT) 10A CONTACT RATING (CURRENT) 10A CONTACT ROMM DEDT (2 Form C) COIL TYPE Non Latching COIL TYPE Non LAtching COIL CURRENT 13.0mA		Specifications of RR2BA-UDC110V
MANUFACTURER DESCRIPTION RELAY GEN PURPOSE DPDT 10A 110V LEAD FREE STATUS / ROHS STATUS LEAD free F ROHS Compliant QUANTITY AVAILABLE 6607 pcs DATA SHEET TURN ON VOLTAGE (MAX) 88 VDC TURN OFF VOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELEASE TIME 25ms RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER		Specifications of RRZBA OBCITOV
DESCRIPTION LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compiliant QUANTITY AVAILABLE 6607 pcs DATA SHEET □ RR2BA-UDC110V.pdf TURN ON VOLTAGE (MAX) 88 VDC TURN ON FVOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect • 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC • Max SERIES RR RELEASE TIME 25ms RELEASE TIME 25ms RELAY TYPE Goneral Purpose PACKAGING OPERATING TEMPERATURE 25ms MOUNTING TYPE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compilant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) CONTACT RATING (CURRENT) COIL YOLTAGE 110VDC COIL YOLTAGE 110VDC COIL TYPE No Latching COIL RESISTANCE 8.46 KOhms COIL POWER -	PART NUMBER	RR2BA-UDC110V
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 6607 pcs DATA SHEET EN RREBA-UDC110V.pdf TURN ON VOLTAGE (MAX) 88 VDC TURN OFF VOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING OTHER NAMES 1885-1469 OPERATING TEMPERATURE 25ms MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS LEAD free F SATUS / ROHS STATUS LEAD free F STATUS / ROHS STATUS LEAD free F ONHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coll Socketable CONTACT MATERIAL Silver (Ag) CONTACT MATERIAL SILVER (AG) CONTACT FORM DPDT (2 Form C) COLL VOLTAGE 110VDC COLL TYPE Non Latching COLL RESISTANCE 8.46 KOhms COLL POWER	MANUFACTURER	IDEC
QUANTITY AVAILABLE DATA SHEET DE RAZBA-UDC110V.pdf SWITCH SHOW SHOW SHOW SHOW SHOW SHOW SHOW SHO	DESCRIPTION	RELAY GEN PURPOSE DPDT 10A 110V
DATA SHEET TURN ON VOLTAGE (MAX) 88 VDC TURN OFF VOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING OPERATING TEMPERATURE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS LEAd free / ROHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT MATERIAL SINVEr (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE NON LEACHING 8.46 KOhms COIL POWER - COIL POWER 110VDC COIL POWER - READ RESESTANCE 8.46 KOhms COIL POWER - COIL POWER 110VDC COIL POWER - COIL POWER 110VDC COIL POWER - LEAD FREE STISTUS (CONTACT MATERIAL COIL POWER - COIL POWER - COIL POWER - READ AND ASSEMBLY (A-7mm) 110 VOLC COIL POWER - COIL TYPE NO IL ASSEMBLY (A-7mm) SRY (4.7mm) COIL FORM COIL POWER - C	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
TURN ON VOLTAGE (MAX) 88 VDC TURN OFF VOLTAGE (MIN) 11 VDC TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING DYFRATING TEMPERATURE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT MATERIAL SIlver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER	QUANTITY AVAILABLE	6607 pcs
TURN OFF VOLTAGE (MIN) TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE 25ms MOUNTING TYPE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER	DATA SHEET	RR2BA-UDC110V.pdf
TERMINATION STYLE Plug In, Quick Connect - 0.187" (4.7mm) SWITCHING VOLTAGE 240VAC, 30VDC - Max SERIES RR RELEASE TIME 25ms RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL VOLTAGE 110VDC COIL RESISTANCE 8.46 kOhms COIL POWER -	TURN ON VOLTAGE (MAX)	88 VDC
SERIES RR RELEASE TIME 25ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL YOLTAGE 110VDC COIL RESISTANCE 8.46 KOhms COIL POWER - COIL POWER - REA OND ACCUMANCE SILVER SILV	TURN OFF VOLTAGE (MIN)	11 VDC
RELASE TIME 25ms RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER -	TERMINATION STYLE	Plug In, Quick Connect - 0.187" (4.7mm)
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER -	SWITCHING VOLTAGE	240VAC, 30VDC - Max
RELAY TYPE General Purpose PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER -	SERIES	RR
PACKAGING DIL PACKAGING Bulk OTHER NAMES 1885-1469 OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER	RELEASE TIME	25ms
OTHER NAMES OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER -	RELAY TYPE	General Purpose
OPERATING TEMPERATURE -25°C ~ 40°C OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER	PACKAGING	Bulk
OPERATE TIME 25ms MOUNTING TYPE Socketable LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL POWER -	OTHER NAMES	1885-1469
MOUNTING TYPE LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER	OPERATING TEMPERATURE	-25°C ~ 40°C
LEAD FREE STATUS / ROHS STATUS FEATURES - DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 KOhms COIL POWER	OPERATE TIME	25ms
FEATURES DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	MOUNTING TYPE	Socketable
DETAILED DESCRIPTION General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable 10A CONTACT RATING (CURRENT) 10A CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
CONTACT RATING (CURRENT) CONTACT MATERIAL Silver (Ag) CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	FEATURES	-
CONTACT MATERIAL CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	DETAILED DESCRIPTION	General Purpose Relay DPDT (2 Form C) 110VDC Coil Socketable
CONTACT FORM DPDT (2 Form C) COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	CONTACT RATING (CURRENT)	10A
COIL VOLTAGE 110VDC COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	CONTACT MATERIAL	Silver (Ag)
COIL TYPE Non Latching COIL RESISTANCE 8.46 kOhms COIL POWER -	CONTACT FORM	DPDT (2 Form C)
COIL RESISTANCE 8.46 kOhms COIL POWER -	COIL VOLTAGE	110VDC
COIL POWER -	COIL TYPE	Non Latching
	COIL RESISTANCE	8.46 kOhms
COIL CURRENT 13.0mA	COIL POWER	-
	COIL CURRENT	13.0mA

Related Tags

· · · · · · · · · · · · · · · · · · ·		
IDEC RR2BA-UDC110V	RR2BA-UDC110V Distributor	RR2BA-UDC110V Supplier
RR2BA-UDC110V Price	RR2BA-UDC110V Pictures	RR2BA-UDC110V Image
RR2BA-UDC110V PDF Datasheet	RR2BA-UDC110V Download Datasheet	RR2BA-UDC110V Datasheet
RR2BA-UDC110V Stock	Buy RR2BA-UDC110V	Buy IDEC RR2BA-UDC110V
IDEC RR2BA-UDC110V	IDEC Supplier	IDEC Distributor
IDEC RR2BA-UDC110V		

Related Products



RR2BA-ULAC240V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 240V In stock: 5204 pcs

RFQ



RR264MM-400TR

Manufacturers: LAPIS Semiconductor Description: DIODE GEN PURP 400V 1A PMDU

In stock: 238752 pcs **RFQ**



RR2BA-UDC24V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 24V

In stock: 6805 pcs

RFQ



RR2BA-ULAC120V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 120V

In stock: 5348 pcs

RFQ



RR268MM-600TR Manufacturers: LAPIS Semiconductor

Description: DIODE GEN PURP 600V 1A PMDU In stock: 201206 pcs

RFQ



RR2BA-UAC240V

Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 240V In stock: 5768 pcs

RFQ



RR2BA-UAC12V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 12V In stock: 6015 pcs

RFQ



RR2BA-UDC12V

Manufacturers: IDEC Description: RELAY GEN PURPOSE DPDT 10A 12V

In stock: 6179 pcs

RFQ



RR2BA-UDC48V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 48V In stock: 6229 pcs

RFQ



RR2BA-ULAC24V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 24V In stock: 4282 pcs

RFQ



RR274EA-400TR Manufacturers: LAPIS Semiconductor

In stock: 188006 pcs

Description: DIODE ARRAY GP 400V 500MA TSMD5

RFQ

Copyright © 2020 Reliable Distributor of Electronic Components



RR2BA-UAC120V Manufacturers: IDEC

Description: RELAY GEN PURPOSE DPDT 10A 120V In stock: 6207 pcs

RFQ



















