

• E-Switch

TL1100AF160Q

Part Number: Manufacturer/Brand:

Product description Datasheets:

Stock Condition Ship From Shipment Way

RoHs Status

TL1100AF160Q

E-Switch

1.TL1100AF160Q.pdf

SWITCH TACTILE SPST-NO 0.05A 12V

2.TL1100AF160Q.pdf Lead free / RoHS Compliant 299373 pcs stock

Hong Kong DHL/Fedex/TNT/UPS/EMS

**REQUEST FOR QUOTATION** 

Image may be representation. See specifications for product details.

PART NUMBER T.LILOOAF 160Q MANUFACTURER E.SWITCH TACTILE SPST-NO 0.05A 12V LEAD FREE STATUS / ROHS STATUS LUMINATION STYLE LEAD FREE STATUS / ROHS STATUS LULMINATION TYPE, COLOR LLUMINATION TYPE, COLOR		
MANUFACTURER         E-Switch           DESCRIPTION         SWITCH TACTILE SPST-NO 0.05A 12V           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           QUANTITY AVAILABLE         299373 pcs           DATA SHEET         LITLI 100AF160Q.pdf           SWITCH TRAVEL         0.30mm           SWITCH FRAVEL         0.30mm           SWITCH FUNCTION         OIF-Hom           SERIES         ILLI 100           PACKAGING         Bulk           OUTLINE         1.20mm x 12.00mm           OPERATING TEMPERATURE         2.00° ~ 70°C           OPERATING TEMPERATURE         1.00m x 12.00mm           MOUNTING TYPE         1.00m x 12.00mm           MECHANICAL LIFE         1.00m x 12.00mm           MEDIANG TYPE         1.00m x 12.00mm           MEDIANG TYPE (MINIA)         1.00m x 12.00mm           ILLUMINATION VOLTAGE (NOMINAL)         1.00m x 12.00mm           ILLUMINATION VOLTAGE (NOMINAL)         1.00m x 12.00mm           ILLUMINATION YPE, COLOR         1.00m x 12.00mm		Specifications of TL1100AF160Q
MANUFACTURER         E-Switch           DESCRIPTION         SWITCH TACTILE SPST-NO 0.05A 12V           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           QUANTITY AVAILABLE         299273 pcs           DATA SHEET         \$\frac{1.11100AF16QQ.pdf}{2.211.1100AF16QQ.pdf}\$           SWITCH FRAVEL         0.3dmm           SWITCH FRAVEL         0.3dmm           SWITCH FRAVEL         0.3dmm           SWITCH FUNCTION         0/f-Mom           SERIES         1L1100           PACAGING         Bulk           OUTLINE         12.00mm x 12.00mm           OPERATING FEMERATURE         -20°C ~ 70°C           OPERATING FEMERATURE         160gf           MOUNTING TYPE         1(Unlimited)           MOUNTING TYPE         1(Unlimited)           MECHANICAL LIFE         10.000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION YOLTAGE (NOMINAL)         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           CERTALLED DESCRIPTION         -           CERTALLED STATUS (SWITCHS)	PART NUMBER	TL1100AF160O
DESCRIPTION         SWITCH TACTILE SPST-NO 0.05A 12V           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           QUANTITY AVAILABLE         299373 pcs           DATA SHEET         In 1.1100AF160Q.pdf           EXPLICATION STYLE         PC Pin           SWITCH TRAVEL         303mm           SWITCH FUNCTION         Off-Mom           SERIES         1.1100           PACXAGING         Bulk           OUTLINE         1.20mm x 12.00mm           OPERATING FORCE         160gf           MOINTING TYPE         Trough Hole           MOINTING TYPE         10,0000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION YPE, COLOR         -           ILLUMINATION OLTAGE (NOMINAL)         -           ILLUMINATION YPE, COLOR         -           CONTACT BATTING & VOLTAGE         0.00 A & 12VDC           CONTACT BATTING & VOLTAGE         0.00 A & 12VDC		
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE QUANTITY AVAILABLE 299373 pc  1.11.1100AF160Q.pdf 2.11.1100AF160Q.pdf 2.11.		
QUANTITY AVAILABLE         29373 pcs           DATA SHEET         21.11.1100AF160Q.pdf           EXPLANTION STYLE         PC PIN           SWITCH TRAVEL         3.00mm           SWITCH FUNCTION         Off-Mon           SERIES         11.100           GOVERATION         12.00mm 12.00mm           OUTLINE         12.00mm 12.00mm           OPERATING TEMPERATURE         -20°C ~ 70°C           OPERATING TEMPERATURE         160gf           MOUNTING TYPE         Through Hole           MOUNTING TYPE         10,0000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           LILLMINATION YUFFA, COLOR         -           LILLMINATION YUPF, COLOR         1-           LILLMINATION YUPF, COLOR         1-           LILLMINATION YUPF, COLOR         1-           EATURES         1-           DETAILED DESCRIPTION         1-           CONTACT RATING & VOLTAGE         0.05A @ 12VDC           CIRCUIT         SPST-NO           ACTUATOR RYPE         Punger for Cap           ACTUATOR ORIENTATION         Top Actuated           ACTUATOR MATERIAL         Polyester     <		
DATA SHEET         I .1.1100AF160Q.pdf           TERMINATION STYLE         PC Pin           SWITCH TRAVEL         0.30mm           SWITCH FUNCTION         Off-Mom           SERIES         TL1100           PACKACING         Bulk           OUTLINE         12.00mm x 12.00mm           OPERATING TEMPERATURE         -20°C ~ 70°C           OPERATING TEMPERATURE         160gf           MOUNTING TYPE         Through Hole           MOLISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         100,000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION VOLTAGE (NOMINAL)         -           IELLUMINATION TYPE, COLOR         Tactile Feedback           DETAILED DESCRIPTION         Tactile		
SWITCH TRAVEL         3.30mm           SWITCH FUNCTION         Off-Mom           SERIES         T.1100           PACKAGING         Bulk           OUTLINE         12.00mm x 12.00mm           OPERATING TEMPERATURE         2.00°C ~ 70°C           OPERATING FORCE         160gf           MOUNTING TYPE         Through Hole           MOISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         100,000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Tactile Feedback           DETAILED DESCRIPTION         Tactile Feedback           CONTACT RATING @ VOLTAGE         0.55 @ 12VDC           CIRCUIT         SPST-NO           ACTUATOR TYPE         Plunger for Cap           ACTUATOR CRIENTATION         Top Actuated		1.TL1100AF160Q.pdf
SERTES         TL1100           PACKAGING         Bulk           OUTLINE         12.00mm x 12.00mm           OPERATING TEMPERATURE         12.00m x 12.00mm           OPERATING FORCE         160gf           MOUNTING TYPE         Through Hole           MOINTING TYPE         100,000 Cycles           MECHANICAL LIFE         100,000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / RoHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           ILLUMINATION TYPE, COLOR         Tactile Feedback           DETAILED DESCRIPTION         Tactile Feedback           CONTACT RATING @ VOLTAGE         0.054 @ 12VDC           CICRUIT         SPST-NO           ACTUATOR TYPE         Plunger for Cap           ACTUATOR CRIENTATION         Top Actuated	TERMINATION STYLE	PC Pin
SERIES         TL1100           PACKAGING         Bulk           OUTLINE         12.00mm x 12.00mm           OPERATING TEMPERATURE         20°C ~ 70°C           OPERATING FORCE         160gf           MOUNTING TYPE         Through Hole           MCISTURE SENSITIVITY LEVEL (MSL)         1 (Unlimited)           MECHANICAL LIFE         100,000 Cycles           LEAD FREE STATUS / ROHS STATUS         Lead free / ROHS Compliant           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION VOLTAGE (NOMINAL)         -           ILLUMINATION TYPE, COLOR         -           FEATURES         Tactile Feedback           DETAILED DESCRIPTION         Tactile Switch SPST-NO Top Actuated Through Hole           CONTACT RATING @ VOLTAGE         0.05A @ 12VDC           CIRCUIT         SPST-NO           ACTUATOR TYPE         Punger for Cap           ACTUATOR ORIENTATION         Top Actuated           ACTUATOR ORIENTATION         Polyester	SWITCH TRAVEL	0.30mm
PACKAGING OUTLINE OUTLINE 12.00mm x 12.00mm OPERATING TEMPERATURE 20°C ~ 70°C OPERATING FORCE 160gf MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 100,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LILUMINATION VOLTAGE (NOMINAL) 1- LILUMINATION TYPE, COLOR 1- LILUMINATION PERATURE DETAILED DESCRIPTION Tacille Switch SPST-NO Top Actuated Through Hole CONTACT RATING @ VOLTAGE ACTUATOR TYPE ACTUATOR NORIENTATION POlyester  ACTUATOR ORIENTATION POlyester Polyest	SWITCH FUNCTION	Off-Mom
OUTLINE12.00mm x 12.00mmOPERATING TEMPERATURE-20°C ~ 70°COPERATING FORCE160gfMOUNTING TYPEThrough HoleMOISTURE SENSITIVITY LEVEL (MSL)1 (Unlimited)MECHANICAL LIFE100,000 CyclesLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATION TYPE, COLORNon-IlluminatedFEATURESTactile FeedbackDETAILED DESCRIPTIONTactile Switch SPST-NO Top Actuated Through HoleCONTACT RATING @ VOLTAGE0.05A @ 12VDCCIRCUITSPST-NOACTUATOR TYPEPlunger for CapACTUATOR ORIENTATION7 PACLUATEDACTUATOR MATERIALPolyester	SERIES	TL1100
POPERATING TEMPERATURE  POPERATING FORCE  BOOGNAME  MOUNTING TYPE  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  1-  LILUMINATION YOLTAGE (NOMINAL)  MON-Illuminated  FEATURES  Tactile Feedback  DETAILED DESCRIPTION  Tactile Switch SPST-NO Top Actuated Through Hole  CONTACT RATING @ VOLTAGE  CIRCUIT  ACTUATOR TYPE  ACTUATOR ORIENTATION  NON-Actuated  Polyester  Polyester	PACKAGING	Bulk
DEPERATING FORCE  MOUNTING TYPE  Through Hole  MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  LILUMINATION TYPE, COLOR  LILUMINATION TYPE, COLOR  LILUMINATION  MON-Illuminated  TEATURES  TACTILE FEEDBACK  DETAILED DESCRIPTION  TACTILE SWITCH SPST-NO TOP Actuated Through Hole  CONTACT RATING @ VOLTAGE  LICUMINATION  ACTUATOR TYPE  ACTUATOR ORIENTATION  TOP Actuated  Plunger for Cap  ACTUATOR ORIENTATION  Polyester	OUTLINE	12.00mm x 12.00mm
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) MECHANICAL LIFE 100,000 Cycles LEAD FREE STATUS / ROHS STATUS LEAd free / RoHS Compliant ILLUMINATION VOLTAGE (NOMINAL) ILLUMINATION TYPE, COLOR ILLUMINATION ILLUMINATION INCRESS PROTECTION ILLUMINATION ILLUMINATION INCRESS PROTECTION ILLUMINATION INCRESS PROTECTION INCRESS	OPERATING TEMPERATURE	-20°C ~ 70°C
MOISTURE SENSITIVITY LEVEL (MSL)  MECHANICAL LIFE  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LEAD FREE STATUS / ROHS STATUS  LILUMINATION VOLTAGE (NOMINAL)  LILUMINATION TYPE, COLOR  LILUMINATION  MON-Illuminated  FEATURES  Tactile Feedback  DETAILED DESCRIPTION  Tactile Switch SPST-NO Top Actuated Through Hole  CONTACT RATING @ VOLTAGE  ACTUATOR TYPE  ACTUATOR STATUS  ACTUATOR NATERIAL  Plunger for Cap  ACTUATOR MATERIAL  Polyester	OPERATING FORCE	160gf
MECHANICAL LIFE100,000 CyclesLEAD FREE STATUS / ROHS STATUSLead free / ROHS CompliantINGRESS PROTECTION-ILLUMINATION VOLTAGE (NOMINAL)-ILLUMINATION TYPE, COLOR-ILLUMINATIONNon-IlluminatedFEATURESTactile FeedbackDETAILED DESCRIPTIONTactile Switch SPST-NO Top Actuated Through HoleCONTACT RATING @ VOLTAGE0.05A @ 12VDCCIRCUITSPST-NOACTUATOR TYPEPlunger for CapACTUATOR ORIENTATIONTop ActuatedACTUATOR MATERIALPolyester	MOUNTING TYPE	Through Hole
LEAD FREE STATUS / ROHS STATUS  Lead free / RoHS Compliant  INGRESS PROTECTION  ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  Tactile Feedback  DETAILED DESCRIPTION  Tactile Switch SPST-NO Top Actuated Through Hole  CONTACT RATING @ VOLTAGE  CIRCUIT  ACTUATOR TYPE  ACTUATOR ORIENTATION  TOP Actuated  ACTUATOR MATERIAL  Polyester	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
INGRESS PROTECTION : CLUMINATION VOLTAGE (NOMINAL) : C.  ILLUMINATION TYPE, COLOR : C.  ILLUMINATION TYPE, COLOR : C.  ILLUMINATION : Non-Illuminated : C.  ILLUMINATION : Tactile Feedback : C.  ICALIED DESCRIPTION : Tactile Switch SPST-NO Top Actuated Through Hole : C.  CONTACT RATING @ VOLTAGE : C.  ICRCUIT : SPST-NO : SPST-NO : C.  ACTUATOR TYPE : Plunger for Cap : C.  ACTUATOR ORIENTATION : Top Actuated : C.  ACTUATOR MATERIAL : Polyester : C.  Polyester	MECHANICAL LIFE	100,000 Cycles
ILLUMINATION VOLTAGE (NOMINAL)  ILLUMINATION TYPE, COLOR  ILLUMINATION  Non-Illuminated  FEATURES  DETAILED DESCRIPTION  Tactile Feedback  CONTACT RATING @ VOLTAGE  CONTACT RATING TYPE  ACTUATOR TYPE  ACTUATOR ORIENTATION  Polyester	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
ILLUMINATION TYPE, COLOR ILLUMINATION Non-Illuminated FEATURES Tactile Feedback DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Through Hole CONTACT RATING @ VOLTAGE 0.05A @ 12VDC CIRCUIT SPST-NO ACTUATOR TYPE Plunger for Cap ACTUATOR ORIENTATION Polyester Polyester	INGRESS PROTECTION	-
ILLUMINATIONNon-IlluminatedFEATURESTactile FeedbackDETAILED DESCRIPTIONTactile Switch SPST-NO Top Actuated Through HoleCONTACT RATING @ VOLTAGE0.05A @ 12VDCCIRCUITSPST-NOACTUATOR TYPEPlunger for CapACTUATOR ORIENTATIONTop ActuatedACTUATOR MATERIALPolyester	ILLUMINATION VOLTAGE (NOMINAL)	-
FEATURES  Tactile Feedback  DETAILED DESCRIPTION  Tactile Switch SPST-NO Top Actuated Through Hole  CONTACT RATING @ VOLTAGE  O.05A @ 12VDC  CIRCUIT  SPST-NO  ACTUATOR TYPE  ACTUATOR ORIENTATION  Top Actuated  Polyester  Polyester	ILLUMINATION TYPE, COLOR	-
DETAILED DESCRIPTION Tactile Switch SPST-NO Top Actuated Through Hole  CONTACT RATING @ VOLTAGE  0.05A @ 12VDC  CIRCUIT  SPST-NO  ACTUATOR TYPE  Plunger for Cap  ACTUATOR ORIENTATION  Top Actuated  Polyester	ILLUMINATION	Non-Illuminated
CONTACT RATING @ VOLTAGE 0.05A @ 12VDC CIRCUIT SPST-NO ACTUATOR TYPE Plunger for Cap ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Polyester	FEATURES	Tactile Feedback
CIRCUIT SPST-NO ACTUATOR TYPE Plunger for Cap ACTUATOR ORIENTATION Top Actuated ACTUATOR MATERIAL Polyester	DETAILED DESCRIPTION	Tactile Switch SPST-NO Top Actuated Through Hole
ACTUATOR TYPE Plunger for Cap  ACTUATOR ORIENTATION Top Actuated  ACTUATOR MATERIAL Polyester	CONTACT RATING @ VOLTAGE	0.05A @ 12VDC
ACTUATOR ORIENTATION Top Actuated  ACTUATOR MATERIAL Polyester	CIRCUIT	SPST-NO
ACTUATOR MATERIAL Polyester	ACTUATOR TYPE	Plunger for Cap
	ACTUATOR ORIENTATION	Top Actuated
ACTUATOR LENGTH, RIGHT ANGLE -	ACTUATOR MATERIAL	Polyester
	ACTUATOR LENGTH, RIGHT ANGLE	-

# **Related Tags**

7.30mm

E-Switch TL1100AF160Q	TL1100AF160Q Distributor	TL1100AF160Q Supplier
TL1100AF160Q Price	TL1100AF160Q Pictures	TL1100AF160Q Image
TL1100AF160Q PDF Datasheet	TL1100AF160Q Download Datasheet	TL1100AF160Q Datasheet
TL1100AF160Q Stock	Buy TL1100AF160Q	Buy E-Switch TL1100AF160Q
E-Switch TL1100AF160Q	E-Switch Supplier	E-Switch Distributor
E-Switch TL1100AF160Q		

# **Related Products**

#### TL1100AF260Q Manufacturers: E-Switch

ACTUATOR HEIGHT OFF PCB, VERTICAL

Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 382277 pcs


**RFQ** 



Manufacturers: Apex Tool Group Description: NUT DRIVER HEX SCKT 5/16" 10.13"

In stock: 10748 pcs **RFQ** 

TL10N



TL1100BF260Q

Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 6676 pcs

**RFQ** 



## TL1100CF160Q

Manufacturers: E-Switch Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 161912 pcs



### **TL104K10R0CE** Manufacturers: Ohmite

Description: RES CHAS MNT 10 OHM 10% 158W In stock: 2429 pcs

**RFQ** 

TL1100BF160Q

### Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 121319 pcs

**RFQ** 





Manufacturers: E-Switch Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 392522 pcs

**RFQ** 



Description: RES CHAS MNT 500 OHM 10% 158W


In stock: 2252 pcs



#### TL104K2K20 Manufacturers: Ohmite

Description: RES CHAS MNT 2.2K OHM 10% 158W In stock: 4637 pcs

**RFQ** 



### TL1100CF160Q.08BLK

Manufacturers: E-Switch Description: SWITCH TACTILE SPST-NO 0.05A 12V

In stock: 105542 pcs **RFQ** 



TL11

Manufacturers: Tripp Lite Description: AC/DC CONVERTER 13.8V 152W In stock: 5366 pcs

**RFQ** 

**Copyright © 2020 Reliable Distributor of Electronic Components** 





Manufacturers: Ohmite Description: RES CHAS MNT 33 OHM 10% 158W In stock: 2867 pcs

**RFQ** 





E-mail: Info@infinity-electronic.com Address: 17F, Gaylord Commercial Building, 114-118 Lockhart Road, Wan Chai, Hong Kong















