C&K



6

C&K

A10215RNZQ

Part Number: Manufacturer/Brand: Product description Datasheets: RoHs Status Stock Condition Ship From Shipment Way

A10215RNZQ

C&K

SWITCH ROTARY 2POS 2.5A 125V

A10215RNZQ.pdf

Lead free / RoHS Compliant

13732 pcs stock Hong Kong

DHL/Fedex/TNT/UPS/EMS

REQUEST FOR QUOTATION

Image may be representation. See specifications for product details.

PART NUMBER AL021SRNZQ MANUFACTURER CAK DESCRIPTION SWITCH ROTARY 2POS 2.5A 125V LEAD FREE STATUS / ROHS STATUS AL021SRNZQ pdf VOUTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A PANEL CUTFOUT DIMENSIONS OTHER NAMES AL021SRNZQ-ND CONILT73 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 2 NUMBER OF POLES FER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE / ROHS Compliant ROHS / ROH		
MANUFACTURER DESCRIPTION SWITCH ROTARY 2POS 2.5A 125V LEAD FREE STATUS / ROHS STATUS LEAD		Specifications of A10215RNZQ
MANUFACTURER DESCRIPTION SWITCH ROTARY 2POS 2.5A 125V LEAD FREE STATUS / ROHS STATUS LEAD	DADT MI IMDED	A1021EDNIZO
DESCRIPTION SWITCH ROTARY 2POS 2.5A 125V LEAD FREE STATUS / ROHS STATUS LEAD free F RoHS Compliant QUANTITY AVAILABLE 13732 pcs DATA SHEET PARTING - DC 125V VOLTAGE RATING - AC 125V VOLTAGE RATING - AC 125V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A AC ALOUISRAVZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROTARY SWItch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CONTACT HINING CONTACT HINING NON-Shorting (BBM) CONTACT FINISH SINCE CRULIT PER DECK SPDT ANGLE OF THROW 30P		
LEAD FREE STATUS / ROHS STATUS QUANTITY AVAILABLE 13732 pcs DATA SHEET 2 A10215RNZQ.pdf VOLTAGE RATING - DC 125V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A PANEL CUTOUT DIMENSIONS CIrcular - 9.80mm Dia A10215RNZQ-NDD CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 1 MOUNTING TYPE Panel Mount MOISTURG SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free / RoHS Compliant INDEX STOPS FREQ DETAILED DESCRIPTION ROLATY SWItch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT FINISH CIRCUIT PER DECK POUT SIEVER SIEVER SIEVER CIRCUIT PER DECK SPDT ANGLE OF THROW 30°		
QUANTITY AVAILABLE 13732 pcs DATA SHEET 6 A10215RNZQ.pdf VOLTAGE RATING - DC 125V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A PANEL CUTOUT DIMENSIONS Circular - 9.80mm Dia OTHER NAMES A10215RNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF POLES PER DECK 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - FURTH BEHIND PANEL 20.33mm CURRENT RATING 2.54 (AC), 350mA (
DATA SHEET VOLTAGE RATING - DC 125V VOLTAGE RATING - AC 125V TERMINATION STYLE SOIDER LUG SERIES A PANEL CUTOUT DIMENSIONS CITCULAR - 9.80mm Dia OTHER NAMES A1021SRNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 MOUNTING TYPE PANEL MOUNTING TYPE PANEL MOUNTING TYPE PANEL MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LOHEN STATUS LOHEN SWINCH 2 POSITION SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT TIMING NON-Shorting (BBM) CONTACT FINISH SIVEY CIRCUIT PER DECK SPDT ANGLE OF THROW 30°		
VOLTAGE RATING - DC VOLTAGE RATING - AC 125V VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A PANEL CUTOUT DIMENSIONS Circular - 9.80mm Dia OTHER NAMES A1021SRNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POSITIONS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Leed free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROLLY SWINCH 2 POSITION SPOT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT FINISH CIRCUIT PER DECK AA A A A A A A A A A A A		
VOLTAGE RATING - AC 125V TERMINATION STYLE Solder Lug SERIES A PANEL CUTOUT DIMENSIONS Circular - 9.80mm Dia OTHER NAMES A10215RNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 MUNDISTURY SPE Panel Mount MOLITING TYPE Panel Mount MOLISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEFTH BEHIND PANEL 20.83mm CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Silver (Ag) CONTACT FINISH Silver CIRCUIT PER DECK SPDT ANGLE OF THROW 30°		
TERMINATION STYLE SERIES A PANEL CUTOUT DIMENSIONS Circular - 9,80mm Dia OTHER NAMES A10215RNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD free / ROHS Compliant INDEX STOPS FEATURES - DETAILED DESCRIPTION ROLSTY SWItch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING NON-Shorting (BBM) CONTACT MATERIAL SINEY CIRCUIT PER DECK ANGLE OF THROW 30° CIRCUIT PER DECK ANGLE OF THROW 30°	VOLTAGE RATING - DC	
PANEL CUTOUT DIMENSIONS CIrcular - 9.80mm Dia OTHER NAMES AL021,SRNZQ-ND CKN11773 OPERATING FORCE - C NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS FIXED FEATURES - C DETAILED DESCRIPTION ROTAGE SENSITIVITY LEVEL (MSL) 20.83mm CURRENT RATING 20.83mm CURRENT RATING Non-Shorting (BBM) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH SINEY CIRCUIT PER DECK SPOPT ANGLE OF THROW 30° CONTACT FINISH SINEY CIRCUIT PER DECK SPOPT ANGLE OF THROW 30° CONTACT FINISH SINEY CIRCUIT PER DECK SPOPT ANGLE OF THROW 30° CONTACT FINISH SINEY CIRCUIT PER DECK SPOPT ANGLE OF THROW 30° CONTACT FINISH SINEY CO	VOLTAGE RATING - AC	125V
PANEL CUTOUT DIMENSIONS CIRCUIAR - 9.80mm Dia A1021SRNZQ-ND CKN11773 CPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION ROtary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT TIMING CONTACT FINISH CIRCUIT PER DECK AND SINVER SPDT ANGLE OF THROW ANGLE OF THROW AIGUIST PASS AND	TERMINATION STYLE	Solder Lug
A10215RNZQ-ND CKN11773 OPERATING FORCE - NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH CIRCUIT PER DECK ANGE OF THROW 30°	SERIES	A
OFERATING FORCE - CKN11773 DEFRATING FORCE - CKN11773 NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / ROHS Compliant INDEX STOPS Fixed - CENTIFICION ROTATION SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL 20.83mm CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Silver (Ag) ANGLE OF THROW 30°	PANEL CUTOUT DIMENSIONS	Circular - 9.80mm Dia
NUMBER OF POSITIONS 2 NUMBER OF POLES PER DECK 1 NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) 1 (Unlimited) LEAD FREE STATUS / ROHS STATUS Lead free / RoHS Compliant INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL 20.83mm CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver (Ag) CONTACT FINISH Silver CIRCUIT PER DECK SPDT ANGLE OF THROW 30°	OTHER NAMES	
NUMBER OF POLES PER DECK NUMBER OF DECKS 1 MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS EATURES DETAILED DESCRIPTION DETAILED DESCRIPTION DEPTH BEHIND PANEL CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMING CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 30° 1 1 1 1 1 1 1 1 1 1 1 1 1	OPERATING FORCE	-
NUMBER OF DECKS MOUNTING TYPE Panel Mount MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTAGN DEPTH BEHIND PANEL CURRENT RATING CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT TIMISH CONTACT FINISH CIRCUIT PER DECK ANGER OF THROW ANGE OF THROW SPDT SOP PANEL ANGE OF THROW ANGE OF THROW PANEL ANGE OF THROW ANGE OF THROW PANEL ANGE OF THROW	NUMBER OF POSITIONS	2
MOUNTING TYPE MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS FEATURES FEATURES DETAILED DESCRIPTION ROTATION ROTAT	NUMBER OF POLES PER DECK	1
MOISTURE SENSITIVITY LEVEL (MSL) LEAD FREE STATUS / ROHS STATUS LEAD FREE STATUS / ROHS STATUS INDEX STOPS Fixed FEATURES - DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Silver (Ag) CURCUIT PER DECK SPDT ANGLE OF THROW 1 (Unlimited) Lead free / ROHS Compliant Lead free / ROHS Compliant Ead free / ROHS Compliant Fixed Fixed Fixed Fixed Fixed Solver Solver (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL 20.83mm CONTACT TIMING Non-Shorting (BBM) CONTACT FINISH Silver CIRCUIT PER DECK SPDT ANGLE OF THROW 30°	NUMBER OF DECKS	1
LEAD FREE STATUS / ROHS STATUSLead free / RoHS CompliantINDEX STOPSFixedFEATURES-DETAILED DESCRIPTIONRotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel MountDEPTH BEHIND PANEL20.83mmCURRENT RATING2.5A (AC), 350mA (DC)CONTACT TIMINGNon-Shorting (BBM)CONTACT MATERIALSilver (Ag)CONTACT FINISHSilverCIRCUIT PER DECKSPDTANGLE OF THROW30°	MOUNTING TYPE	Panel Mount
FINDEX STOPS FIXED FEATURES - DETAILED DESCRIPTION ROTARY Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL 20.83mm CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL Silver (Ag) CONTACT FINISH CIRCUIT PER DECK SPDT ANGLE OF THROW SILVER SI	MOISTURE SENSITIVITY LEVEL (MSL)	1 (Unlimited)
FEATURES DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount DEPTH BEHIND PANEL CURRENT RATING CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW PARABATH AS THROW ROTAGY SWITCH AS THROW ROT	LEAD FREE STATUS / ROHS STATUS	Lead free / RoHS Compliant
DETAILED DESCRIPTION Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount 20.83mm CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount 20.83mm 20.83mm Silver (AC), 350mA (DC) Silver (AG) Silver (Ag) Silver Silver 30° 30°	INDEX STOPS	Fixed
DEPTH BEHIND PANEL CURRENT RATING 2.5A (AC), 350mA (DC) CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 20.83mm 20.8	FEATURES	-
CURRENT RATING CONTACT TIMING Non-Shorting (BBM) CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW 2.5A (AC), 350mA (DC) Non-Shorting (BBM) Silver (Ag) Silver (Ag) SPDT 30°	DETAILED DESCRIPTION	Rotary Switch 2 Position SPDT 2.5A (AC), 350mA (DC) 125VAC Panel Mount
CONTACT TIMING CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Non-Shorting (BBM) Silver (Ag) Silver (Ag) Silver Silve	DEPTH BEHIND PANEL	20.83mm
CONTACT MATERIAL CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Silver (Ag) Silver SPDT 30°	CURRENT RATING	2.5A (AC), 350mA (DC)
CONTACT FINISH CIRCUIT PER DECK ANGLE OF THROW Silver SPDT 30°	CONTACT TIMING	Non-Shorting (BBM)
CIRCUIT PER DECK SPDT ANGLE OF THROW 30°	CONTACT MATERIAL	Silver (Ag)
ANGLE OF THROW 30°	CONTACT FINISH	Silver
	CIRCUIT PER DECK	SPDT
ACTUATOR TYPE Flatted (6.35mm Dia)	ANGLE OF THROW	30°
	ACTUATOR TYPE	Flatted (6.35mm Dia)
ACTUATOR LENGTH 38.10mm	ACTUATOR LENGTH	38.10mm

Related Tags

C&K A10215RNZQ	A10215RNZQ Distributor	A10215RNZQ Supplier
A10215RNZQ Price	A10215RNZQ Pictures	A10215RNZQ Image
A10215RNZQ PDF Datasheet	A10215RNZQ Download Datasheet	A10215RNZQ Datasheet
A10215RNZQ Stock	Buy A10215RNZQ	Buy C&K A10215RNZQ
C&K A10215RNZQ	C&K Supplier	C&K Distributor
C&K A10215RNZQ	C&K Components A10215RNZQ	

Related Products



A10212007CA Manufacturers: Bussmann (Eaton)

Description: CONN BARRIER STRP 20CIRC 0.325" In stock: 5564 pcs

RFQ



A10215RNMCQK Manufacturers: C&K

Description: SWITCH ROTARY 2POS 2.5A 125V

In stock: 11994 pcs

RFQ



A10220207CA

Manufacturers: Bussmann (Eaton) Description: CONN BARRIER STRIP 2CIRC 0.325"

In stock: 6783 pcs

RFQ



A102202S2011 Manufacturers: Bussmann (Eaton)

Description: CONN BARRIER STRIP A1000 SER In stock: 6915 pcs

RFQ



A10212207

Manufacturers: Bussmann (Eaton) Description: CONN BARRIER STRP 22CIRC 0.325"

In stock: 16685 pcs

RFQ



A10215RNMCG

Manufacturers: C&K

Description: SWITCH ROTARY 2POS 2.5A 125V In stock: 8653 pcs

RFQ



A10220207 Manufacturers: Bussmann (Eaton)

Description: CONN BARRIER STRIP 2CIRC 0.325" In stock: 99801 pcs

RFQ



A102202 Manufacturers: Bussmann (Eaton)

Description: CONN BARRIER STRIP 2CIRC 0.325" In stock: 126711 pcs

RFQ



Manufacturers: Bussmann (Eaton) Description: CONN BARRIER STRIP 2CIRC 0.325"

A10220207L5

In stock: 83629 pcs

RFQ



F:T•N

A10212007

Manufacturers: Bussmann (Eaton) Description: CONN BARRIER STRP 20CIRC 0.325" In stock: 16141 pcs

RFQ



A10214MNCQE Manufacturers: C&K

Description: SWITCH ROTARY 2POS 2.5A 125V In stock: 17442 pcs

RFQ



A102203

Manufacturers: Bussmann (Eaton)

Description: CONN BARRIER STRIP 3CIRC 0.325"







In stock: 92443 pcs

RFQ







Copyright © 2020 Reliable Distributor of Electronic Components